


LIMITED EDITION!

CED48206
CED72206

EA-6B

Prowlers Part 2



Recommended kit:
Monogram EA-6B

Cutting Edge

P.O. Box 3956
Merrifield, VA 22116
USA

MODELWORKS www.meteorprod.com


CED48206

Prowlers Part 2



EA-6B

Bu No 163526
Cdr. Bob Stuart CO
VAQ-141
USS JOHN F. KENNEDY
CVW-8




EA-6B

Bu No 162934
Capt. Rodger Welch, CAG
Capt. Dana "Smudge" Potts, DCAG
USS GEORGE WASHINGTON
VAQ-132



**Cutting
Edge**
MODELWORKS



Standard position of top wing numbers

Standard position of top wing numbers

available from

Meteor

Productions
Inc.

P.O. Box 3956, Merrifield, VA 22116 USA
☎ 703/971-0500 FAX 703/971-8111

www.meteorprod.com

Write, call, or visit our home page to order our 120+ page catalog of decals, kits, conversions, tools, books, magazines, etc., and we'll send it to you right away!

© Cutting Edge Modelworks, 2002

EA-6B Prowlers Part 2



CED48206
CED72206

163526

- Note that another aircraft from this unit carried these same markings (including the gunfighter), but was BuNo 164402 from the USS THEODORE ROOSEVELT. While they appear identical, the tail birds were different!
- Apply the tail bird main pieces, then the cap pieces over the antenna cutouts.

Applying the Decals

You probably already know all this stuff, so feel free to use your regular process; however, if you're new to aftermarket decals, here goes:

- Generally, use the Microscale Finishing System. We don't recommend extremely strong decal solvents such as Solvaset.
- Your model must have a smooth, glossy surface, as decals won't adhere well to matte surfaces. Use gloss paints or your favorite clear gloss overspray over matte or semigloss paint.
- Cut each subject out without trimming off the slight excess film (this helps the decal film disappear when dry).
- Put the decal in warm water that has a drop or two of liquid dishwashing soap or photo-flo for 10 seconds.
- When the decal will slide off the backing paper without forcing it, apply it to the proper position on your model. Slide the backing paper out from underneath.
- Gently blot off excess water and smooth out bubbles under the decal surface. If you wish, carefully brush on a mild decal softener such as Micro-Sol.
- When all decals are completely dry, gently wash off all excess decal adhesive.
- Finally, overcoat your model with a good quality gloss coat, followed by your choice of matte or eggshell clear topcoat.

FS 595 Color Cross Reference

- FS 5237 Xtracolor X126, Modelmaster 1721, Mr Color 337, Gunze Sangyo H337
FS 6320 Xtracolor X135, ModelMaster 1741, Gunze Sangyo H307, Mr Color 307, Polly-S 837, Pro Modeler 88-0036, Floquil 303133
FS 6375 Pro Modeler 88-0034, Polly Scale 505304

Bibliography

Original photos.

Special thanks to Capt Dana "Smudge" Potts and Bryan Wilburn!!