

SPECIFICATION

GENERAL:

DESIGNATION; MITTLERER GEPANZERTER MANNSCHAFTKRAFTWAGEN. DESIGNA-TION FROM 1942: MITTLERER SCHUETZENPANZERWAGEN, ORDNANCE No. SdKfz 251. MANUFACTURER'S TYPE: HANOMAG HL kl 6p.

KIT 8022

CREW: 12-COMMANDER, DRIVE, 10 MEN INFANTRY SQUAD, IN BASIC SdKfz 251/1.

BATTLE WEIGHT: 8.9 LONG TONS. DRY WEIGHT: 7.4 TONS.

DIMENSIONS

LENGHT OVERALL: 19 ft. (AUSF. A, B AND C). 19 ft. 71/2 in. AUSF. D.

HEIGHT: 5 ft. 9 in.

WIDTH: 6 ft. 11 in.
WIDTH OVER TRACKS/OVERALL: 6 ft. 11 in.

TRACK CENTRES/WHEEL BASE: 5 ft. in./5 ft. 3 in. TRACK WIDTH: 91/4 in.

ARMAMENT

TWO MG 34 7.92 mm.

SIX 28/32 cm. ROCKETS IN THEIR CRATES ON A FRAME DESIGNED TO CARRY

THREE PROJECTILES ON EACH OF THE VEHICLE.

IN TRANSIT THE ROCKETS WERE STOWED INSIDE THE VEHICLE. NORMALLY THE LOAD CONSISTED OF FIVE 28 cm ROCKETS AND ONE 32 cm. INCENDIARY.

MAYBACH "HL 42 TUKRM" OR TUKRRM. PETROL. 6 CYL. IN-LINE. 4,171 c.c. 100 b.h.p. AT 2,800 r.p.m. FUEL: 35 GALLONS IN ONE TANK BETWEEN FRAME.

ESCI

DESTOC MADE IN ITALY

PERFORMANCE

MAX. ROAD SPEED: 33 m.p.h. MAX. GRADIENT: 24°. TRENCH: 6 ft. 6 in. WADING DEPTH: 2 ft. FUEL CONSUMPTION 3-5 m.p.g.















