

# 2



A/C Type	Bf-109F-4 Trop.
Pilot & Unit	Unteroffizier Franz Schwaiger, 6./JG3.
Locale & Date	Castel Benito, Libya February,
Camouflage & Markings	Standard North Africa Camouflage of RLM 79 over 78

tip. White fuselage bands. Notice that this A/C lacks white wing tips, which was unusual for Remarks

an A/C in this particular theatre. The pilot of this A/C scored 67 kills and achieved the rank of Staffelkapitan, before losing his life on April 24, 1944.

A/C Type	Bf-109F-4 Trop.
Pilot & Unit	Lt. Hans-Amold Stahlschmidt, Staffelkapitan, 2./JG 27.
Locale & Date	Quotaifiya, Egypt. August, 1942.
Camouflage & Markings	Overall RLM 79 with RLM 78 undersurfaces and lower cowling. White spinner, fuselage bands, and wing tips.
Remarks	One of the most successful pilots

the Western Desert. Stahlschmidt was credited with 59 kills before he himself was killed on September 7, 1942. Number 4 may have been outlined in Black. Impossible to see in our photos.

A/C Type	Bf-109F-4 Trop.
Pilot & Unit	Hauptmann Wolfgang Lippert, Gruppenkommandeur II./JG 27.
Locale & Date	Ain El Gazala, Libya. Nov., 1941.
Camouflage & Markings	Standard Camouflage of RLM 79 over 78. Spinner: 1/3 White, 2/3 RLM 70; fuselage band, and wing tips are White.

7

Lippert was shot down in this A/C on Nov. 23, 1941, after detroying a "Hurricane". Bailing out broke both legs and was taken prisoner. He died in a Cairo hospital, following a leg amputation on Dec. 3,


Remarks


A/C Type	Bf-109F-4 Trop.
Pilot & Unit	Oberfeldwebel Otto Schulz, 6./JG 27.
Locale & Date	Tmimi, Libya. May, 1942.
Camouflage &	As A/C 3.


in in in its	
Remarks	Totaled 51 kills before falling
	victim to a Kittyhawk near Sisi
	Rezegh on June 17, 1942. Pilot
	known as Ein-Zwei-Drei Otto.

A/C Type	Bf-109F-4 Trop.
Unit	9./ JG 53, "Pik As".
Locale & Date	Libya. 1942.
Camouflage & Markings	Overall RLM 79 with RLM 78 undersurfaces. White spinner, fuselage band, and wing tips.
Remarks	A/C lost on June 12, 1942 while

Herkenhorff.








Note: All these A/C had the deeper oil cooler(Bf-109F-4). Armour glass on windscreen not common on desert 109s, because grit became trapped between panels.


## OVER THE SAHARA

Color Swatches



We are uncertain as to wether or not A/C 2, 5 and 6 had White upper wing tips. Notice W.Nr. usually appears on left side only. Extras provided.






cachus on the net! Www.EagleStrikeProductions


II./JG 27's 109Fs, the first in N. Africa carried lower Yellow cowls on both Staff and 4, 5 and 6 staffel machines, Nov. 1941.

# Ph: (786) 293-6859, Fax: (786) 293-9286

## References:

- 1-. Bf-109 Aces of North Africa and the Mediterranean, by Jerry Scutts. Osprey Publishing.
- 2-. Bf-109F. Wydawnictwo Militaria, by Janusz Ledwoch.
- 3-. Bf-109 im Einsatz bei Stab und I./JG 27, by J. Prien, P. Rodeike and G. Stemmer.
- 4-. Bf-109 im Einsatz bei Stab und II./JG 27. by J. Prien, P. Rodeike and G. Stemmer.
- 5-. "Pik As" Geschichte des JG 53, Teil 2, by J. Prien.





Our thanks to George Morrison for his invaluable knowledge and unselfish help.

Jank you George

Decaling: Apply decals only to a glossy surface.

- 1. With a sharp scissors or knife, carefully cut item to be used, being careful of not cutting off the clear film around it or that belonging to an adjacent item.
- 2. Submerge in clean tap water for over 10 seconds and lay over an absorbent paper towel. Decal will slide freely in about 20 seconds. Do not leave decal on water bowl over ten seconds, or adhesive quality will suffer.
- 3. With a clean brush, apply a setting solution to the area where the decal will finally lay. (Micro, Super or Aero Set will do). With a clean pointed brush slide the decal on to the final area. Allow the setting solution to dry for about 3-5 minutes.
- 4. With another clean brush, apply a solvent solution over the decal (Micro, Super or Aero Sol will do). Do this if possible in one stroke since your decal will soften up and wrinkle immediately. This is an important step in the process, whatever you do DO NOT TOUCH THE DECAL, after this process until it is totally dry, preferably overnight.
- 5. When thoroughly dry, rinse your model with tap water and mild soap to wash of excess glue.
- 6. Finish your model with the desired final coat (gloss, flat, or semi-gloss).