



Me-262 STURMBİROS Pt. 1



Nowotny in October, 1944. Notice plain White swastika.




Me-262 STURMBIROS Pt. 1




8(8) Two per nacelle or just outboard?

Copyright © 5/2000



28(28)




A/C Type	Me-262A-1A. W. NR. 170067.
Pilot & Unit	Unknown, EKDO.262.
Locale & Date	See A/C 6.
Camouflage & Markings	See A/C 6.

38+39· (38+39)

29(29)


A/C Type	Me-262A-A. W. NR. 170179.
Pilot & Unit	Unknown, Kommando Schenk.
Locale & Date	Chateaudun, July 1944.
Camouflage & Markings	Very undefined camouflage of RLM 74/75 over RLM 76, Red nose cap. A/C equipped with

Remarks




A/C Type	Me-262A-1A, Black D.
Pilot & Unit	As A/C 8.
Locale & Date	Possibly as A/C 8.
Camouflage & Markings	RLM 74/75 over RLM 76.
Remarks	One of the first A/C of the Jet Bomber Unit, Kommando Schenk.

A/C Type	Me- 262 A-1A, White 4.
Pilot & Unit	Unknown, Kommando Nowotny.
Locale & Date	Achmer, Late 1944.
Camouflage & Markings	RLM 81/82 over RLM 76, with possible RLM 70 hard edge splotching on fin & rudder. Yellowband on fuselage. See left nacelle on inst. # 3.
Remarks	Notice Natural Metal engine intakes and Gray (RLM 75?) upper left engine cowling. Rear of engine is Black.




38+39 (38+39)	
35(35)	V303
	34(Both Sides) Bomb Rack

A/C Type	Me-262 V7 W. NR. 130303
Pilot & Unit	Unknown, test unit.
Locale & Date	Unknown.
Camouflage & Markings	RLM 81/82 over RLM 76 . Hard edge splotching on fin & rudder. Natural Metal engine nacelles.
Remarks	Notice replacement tail on this A/C.



(for A/C 10)

Classic miss Publication's Me-262 Vol. II. Pictures of all these aircraft are within. A must if you are a "Sturmbirdaholic!"



References:

1/48th Scale Me-262

Me-262 Volume II, Classic **Publishers**

Decaling: Apply decals only to a glossy surface.

- 1. With a sharp scissors or knife, carefully cut item to be used, being careful of not cutting off the clear film around it or that belonging to an adjacent item.
- 2. Submerge in clean tap water for over 10 seconds and lay over an absorbent paper towel. Decal will slide freely in about 20 seconds. Do not leave decal on water bowl over ten seconds, or adhesive quality will suffer.
- 3. With a clean brush, apply a setting solution to the area where the decal will finally lay. (Micro, Super or Aero Set will do). With a clean pointed brush slide the decal on to the final area. Allow the setting solution to dry for about 3-5 minutes.
- 4. With another clean brush, apply a solvent solution over the decal (Micro, Super or Aero Sol will do). Do this if possible in one stroke since your decal will soften up and wrinkle immediately. This is an important step in the process, whatever you do DO NOT TOUCH THE DECAL, after this process until it is totally dry, preferably overnight.
- 5. When thoroughly dry, rinse your model with tap water and mild soap to wash of excess glue.
- 6. Finish your model with the desired final coat (gloss, flat, or semi-gloss).