

F-35A/B Lightning II **USAF/USMC** Collection





Xtracolor or Xtracrylix paints. Cut out the decal required and soak in warm water until the decal is released from the backing paper. Wet the area to be decaled with MICRO SET which will help to eliminate air trapped under the decal and position the decal. After 5 or 10 minutes wet the decal with MICRO SOL which will soften the decal and ensure that it settles down over any surface detail. Allow the decal to dry for at least 12 hours. During this time some wrinkling of the decal may occur, this is normal. Do not touch the decal at this time. Carefully check for small air bubbles and if there are any prick with a needle and apply a drop of

MICRO SOL. After all air bubbles have been eliminated and the decals are dry wash the entire model

For the best results these decals should be applied to a gloss surface such as provided by either


with water to remove any excess decal adhesive. When completely dry the whole model should be sprayed with a coat of Xtracolor or Xtracrylix Flat, Satin or Gloss varnish depending on the finish required.





Harbour Road, Oulton Broad, Lowestoft, Suffolk, NR32 3LZ


Phone +44 1502 517444 +44 1502 500521 Fax


sales@hannants.co.uk



































Paints:

Xtracolor Paints X133 FS36270 Neutral Grey X504 Exhaust The colours used on these aircraft can be found in the Xtracolor (prefix number with X) and Xtracrylix (prefix number with XA1) range of paints.

Xtracrylix Paints XA1133 FS36270 Neutral Grey