Model Alliance Decals - UK & The Aviation Workshop are trading names of The Aviation Workshop Publications Ltd & Gary Madgwick.

The On-Target Publications, AlRframe Journal, Spot-Lights & Conflict (AirWars are all names registered to The Aviation Workshop Publications Ltd and may not be used without the permission in writing of the The Aviation Workshop Publications Ltd.


These decals and all artwork are copyright The Aviation Workshop Publications Ltd 2009

## **Decals Instructions:**

These decals are a high quality product produced for Model Alliance Decals - UK by Cartograf Italy. The decals are very thin but very strong and flexible.

- 1. Before painting the model, clean with 'Model Wipes'. This cleans the grease and any dust from
- 2. We recommend that you wear 'Model Gloves' to handle the model whilst preparing it for painting.
- 3. For best results, spray the model with a Light Grey primer, any defects can then be made good.
- 4. For demarcation and camouflage lines, we recommend that you use Masking Film.
- If you wish to use a decal fixing and finishing system, we recommend you use the Microscale System, do not use strong decals solvents such as Solvaset.
- 6 Once you are happy with the painting of the model, coat it in a clear gloss finish, this can either be over the entire model if the model is finished glossy or spot gloss finish in the area's that have a decal. A good surface finish are clear floor shine's such as Johnson wax Klear. This is sold under different names around the world. Klear can be either brushed on or sprayed.
- 7. Cut each decal from the sheet as needed. Do not trim the clear varnish finish to close to the decal. Submerge the decal in warm water for about 10 seconds and remove to a flat surface and wait for the decal to release from the backing sheet. A small amount of washing up liquid in the warm water helps the decal release from the sheet.
- 8. These decals do not require a decal setting solution to lay flat or to conform to the model contours.
- With a pair of tweezers to hold the backing sheet, slide the decal in position on the model using a small soft brush. Do not use an old painting brush as bits can get under the decal.
- 10. Carefully remove any excess water with a soft cloth or tissue once you are happy with the position of the decal. Should you make a mistake, dip a brush in the warm water and ease under the edge of the decal. The decal will then easily move to the correct position and again remove the excess water.
- 11. When the decals are completely dry, gently wipe off all excess decal adhesive.
- 12. Leave the model to dry completely, spray or paint over the decals with a further coat of Klear or gloss.
- 13. Should the decal silver for any reason, this is because small air bubbles are under the decal. If found, prick with a pin and apply a small drop of Micro Sol to the decal and allow to dry for up to 12 hours.
- 14. Finally, coat the model with the required finish, either gloss, semi gloss or matt.
- remaily, coat the model with the required finish, either gloss, semi gloss or matt.
   Decals are best stored flat and in a cool, dry place and should not be stored in direct sunlight, hot or humid conditions.
- 16. Should you have any problems with these decals please contact us at the address below.







Watermill Studio, Unit 13/14A, Home Farm, Ardington, Wantage, Oxon, OX12 8EP, UK www.theaviationworkshop.co.uk

Email: info@theaviationworkshop.co.uk








52, 62 or 67 as required

71










UAE F-16F Photos by JV Aviation






F-16F Photo above via USAF Nellis AFB






30+4.2

German AF Eurofighter Photos by Simov Svetlan









VH-60 Photos via USMC/DoD



French Navy Hawkeye Photo right by Robin Powney



RAAF F/A-18 Photos by Phil Vabre



